



Paving Brick Dimensions, Weights, and Coverage

Name	Depth (D)		Height (H)		Length (L)		Weights		Units/ft ²		Packaging	
	in	mm	in	mm	in	mm	lbs	kg	Units/ft ²	Units/m ²	Type	QTY
True Split Paver 4 x 1 1/4 x 8	4	102	1 1/4	32	8	203	2.7	1.2	4.5	48.4	Pallet	664
Modular Split Paver 4 x 1 1/4 x 8	3 5/8	92	1 1/4	32	7 5/8	194	2.5	1.1	4.5	48.4	Pallet	664
Modular Paver 4 x 2 1/4 x 8	3 5/8	92	2 1/4	57	7 5/8	194	4.5	2.0	4.5	48.4	Cube	500
True Paver 4 x 2 1/4 x 8	4	102	2 1/4	57	8	203	5.2	2.3	4.5	48.4	Cube	500
Back Up Pavers 4 x 2 1/4 x 8	3 5/8	92	2 5/8	67	7 5/8	194	4.5	2.0	3.0	32.3	Cube	384

The Above Brick Manufactured by Interstate Brick comply with the following Specifications:

1. ASTM C902: Type I, II or III; Class SX; Application PS, PX, or PA; as specified in Purchase Order
2. ASTM C1272: Type R for 2 1/4" thick; Type F for 2 5/8" thick; Application PS, PX or PA as specified in Purchase Order