



Paving Brick Dimensions, Weights and Coverage

Description	Depth (D)		Height (H)		Length (L)		Weights		Units/Ft <sup>2</sup>		Packaging	
	in	mm	in	mm	in	mm	lbs.	kg.	Units/ft <sup>2</sup>	Units/ft <sup>2</sup>	Type	QTY
1 ¼ Split Modular Paver	3 ⅝	92	1 ¼	32	7 ⅝	194	2.3	1.0	4.5	48.4	Pallet	664
1 ¼ Split True Paver	4	102	1 ¼	32	8	203	2.7	1.2	4.5	48.4	Pallet	664
2 ¼ Modular Paver	3 ⅝	92	2 ¼	57	7 ⅝	194	4.2	1.9	4.5	48.4	Cube	500
2 ¼ True Paver	4	102	2 ¼	57	8	203	5.4	2.5	4.5	48.4	Cube	500
2 ⅝ Vehicular Mod Paver	3 ⅝	92	2 ⅝	67	7 ⅝	194	4.9	2.2	4.5	48.4	Cube	420
2 ⅝ Vehicular True Paver	4	102	2 ⅝	67	8	203	6.3	2.9	4.5	48.4	Cube	420

The Above Brick Manufactured by Interstate Brick comply with the following Specifications:

**ASTM C652:** Grade SW; Type HBA, HBS or HBX as specified in Purchase Order

**CSA A82:** Grade EG; Type A, S or X as specified in Purchase Order