



Atlas® Brick Dimensions, Weights and Coverage

Description	Depth (D)		Height (H)		Length (L)		Weights		Units/Ft ²		Packaging	
	in	mm	in	mm	in	mm	lbs.	kg.	Units/ft ²	Units/ft ²	Type	QTY
4 x 4 x 12 Atlas®	3 5/8	92	3 9/16	90	11 5/8	295	7.5	3.4	3	32.3	Pallet	207
4 x 2 1/4 x 16 Atlas®	3 5/8	92	2 1/4	57	15 5/8	397	7	3.2	3.4	36.6	Pallet	240
4 x 4 x 16 Atlas®	3 5/8	92	3 9/16	90	15 5/8	397	11	5.0	2.25	24.2	Pallet	160
4 x 8 x 16 Atlas®	3 5/8	92	7 9/16	192	15 5/8	397	21.5	9.8	1.125	12.1	Pallet	64
6 x 4 x 12 Atlas®	5 5/8	143	3 9/16	90	11 5/8	295	10	4.5	3	32.3	Pallet	120
6 x 2 1/4 x 16 Atlas®	5 5/8	143	2 1/4	57	15 5/8	397	10	4.5	3.4	36.6	Pallet	120
6 x 4 x 16 Atlas®	5 5/8	143	3 9/16	90	15 5/8	397	14.5	6.6	2.25	24.2	Pallet	100
6 x 8 x 16 Atlas®	5 5/8	143	7 9/16	192	15 5/8	397	34	15.5	1.125	12.1	Pallet	50
8 x 4 x 12 Atlas®	7 5/8	194	3 9/16	90	11 5/8	295	14	6.4	3	32.3	Pallet	100
8 x 2 1/4 x 16 Atlas®	7 5/8	194	2 1/4	57	15 5/8	397	12.7	5.8	3.4	36.6	Pallet	96
8 x 4 x 16 Atlas®	7 5/8	194	3 9/16	90	15 5/8	397	17.2	7.8	2.25	24.2	Pallet	80
8 x 8 x 16 Atlas®	7 5/8	194	7 9/16	192	15 5/8	397	39.2	17.8	1.125	12.1	Pallet	40
10 x 2 1/4 x 16 Atlas®	9 5/8	244	2 1/4	57	15 5/8	397	16.1	7.3	3.4	36.6	Pallet	72
10 x 4 x 16 Atlas®	9 5/8	244	3 9/16	90	15 5/8	397	22.3	10.1	2.25	24.2	Cube	60

The Above Brick Manufactured by Interstate Brick comply with the following Specifications:

ASTM C652: Grade SW; Type HBA, HBS or HBX as specified in Purchase Order

CSA A82: Grade EG; Type A, S or X as specified in Purchase Order